

# Datasheet

COMPOSITE POLYPROPYLENE- PPC-V2

## Technical Corrugated Pipe PPC-V2



- **Application**

For cabling and electrical harnesses used in the automotive industry, machinery industry, automation, among others.

- **Characteristics**

Flexible product, with excellent mechanical resistance, and low abrasion.



- **Flammability**

Flammability V2 according to international standard UL94.

- **Temperature**

Working Temperature: -40°C + 105°C (peak 125°C).



- **Color**

Tubes in black color. Other colors, upon request.

# Datasheet

## COMPOSITE POLYPROPYLENE - PPC-V2

### Technical Corrugated Pipe PPC-V2



Diameter	Code with slit/ unslit	Ø Internal (mm)	Ø External (mm)
<b>4,5</b>	100104-200 / 200104-200	5,00 ± 0,30	7,10 ± 0,30
<b>6</b>	100106-200 / 200106-200	6,00 ± 0,30	9,20 ± 0,30
<b>7,5</b>	100107-200 / 200107-200	6,90 ± 0,30	9,90 ± 0,30
<b>8,5</b>	100108-100 / 200108-100	8,50 ± 0,30	11,60 ± 0,30
<b>9</b>	100109-100 / 200109-100	8,70 ± 0,30	12,90 ± 0,30
<b>10</b>	100110-100 / 200110-100	10,10 ± 0,30	12,90 ± 0,30
<b>11</b>	100111-100 / 200111-100	11,70 ± 0,30	15,20 ± 0,30
<b>11HW</b>	1001H1-100 / 2001H1-100	11,00 ± 0,30	15,70 ± 0,30
<b>12</b>	100112-100 / 200112-100	12,00 ± 0,30	15,60 ± 0,30
<b>1/2"</b>	1001P2-100 / 2001P2-100	12,70 ± 0,30	17,20 ± 0,30
<b>13</b>	100113-100 / 200113-100	12,90 ± 0,30	15,80 ± 0,30
<b>14</b>	100114-100 / 200114-100	14,50 ± 0,30	18,50 ± 0,30
<b>16</b>	100116-100 / 200116-100	15,20 ± 0,30	18,80 ± 0,30
<b>17</b>	100117-100 / 200117-100	16,80 ± 0,40	21,00 ± 0,40
<b>19</b>	100119-100 / 200119-100	19,40 ± 0,40	24,00 ± 0,40
<b>22</b>	100122-100 / 200122-100	21,80 ± 0,40	25,50 ± 0,40
<b>23</b>	100123-100 / 200123-100	23,70 ± 0,40	28,30 ± 0,40
<b>25</b>	100125-100 / 200125-100	25,40 ± 0,40	29,50 ± 0,40
<b>26</b>	100126-100 / 200126-100	26,00 ± 0,40	32,50 ± 0,40
<b>29</b>	100129-050 / 200129-050	29,30 ± 0,40	33,90 ± 0,40
<b>31</b>	100131-050 / 200131-050	31,20 ± 0,40	38,20 ± 0,40
<b>37</b>	100137-050 / 200137-050	37,00 ± 0,40	42,00 ± 0,50
<b>38</b>	100138-050 / 200138-050	38,00 ± 0,50	47,00 ± 0,50
<b>50S</b>	10015S-050 / 20015S-050	47,40 ± 0,50	53,10 ± 0,50
<b>50</b>	100150-050 / 200150-050	50,00 ± 0,50	56,50 ± 0,50