

Datasheet

POLYPROPYLENE - PPC V2 UV

Technical Corrugated Pipe PPC V2 UV



- **Application**

For cabling and electrical harnesses used in the automotive industry, machinery industry, automation, among others.

- **Characteristics**

Product with high flexibility, good mechanical resistance, low abrasion, and anti-UV protection.



- **Flammability**

Flammability V2 according to international standard UL94.

- **Temperature**

Working Temperature: -40°C + 105°C (peak 125°C).



- **Color**

Tubes in black color. Other colors, upon request.

Datasheet

POLYPROPYLENE - PPC V2 UV

Technical Corrugated Pipe PPC V2 UV



Diameter	Code with slit/ unslit	Ø Internal (mm)	Ø External (mm)
4,5	105104-200 / 205104-200	5,00 ± 0,30	7,10 ± 0,30
6	105106-200 / 205106-200	6,00 ± 0,30	9,20 ± 0,30
7,5	105107-200 / 205107-200	6,90 ± 0,30	9,90 ± 0,30
8,5	105108-100 / 205108-100	8,50 ± 0,30	11,60 ± 0,30
9	105109-100 / 205109-100	8,70 ± 0,30	12,90 ± 0,30
10	105110-100 / 205110-100	10,10 ± 0,30	12,90 ± 0,30
11	105111-100 / 205111-100	11,70 ± 0,30	15,20 ± 0,30
11HW	1051H1-100 / 2051H1-100	11,00 ± 0,30	15,70 ± 0,30
12	105112-100 / 205112-100	12,00 ± 0,30	15,60 ± 0,30
1/2"	1051P2-100 / 2051P2-100	12,70 ± 0,30	17,20 ± 0,30
13	105113-100 / 205113-100	12,90 ± 0,30	15,80 ± 0,30
14	105114-100 / 205114-100	14,50 ± 0,30	18,50 ± 0,30
16	105116-100 / 205116-100	15,20 ± 0,30	18,80 ± 0,30
17	105117-100 / 205117-100	16,80 ± 0,40	21,00 ± 0,40
19	105119-100 / 205119-100	19,40 ± 0,40	24,00 ± 0,40
22	105122-100 / 205122-100	21,80 ± 0,40	25,50 ± 0,40
23	105123-100 / 205123-100	23,70 ± 0,40	28,30 ± 0,40
25	105125-100 / 205125-100	25,40 ± 0,40	29,50 ± 0,40
26	105126-100 / 205126-100	26,00 ± 0,40	32,50 ± 0,40
29	105129-050 / 205129-050	29,30 ± 0,40	33,90 ± 0,40
31	105131-050 / 205131-050	31,20 ± 0,40	38,20 ± 0,40
37	105137-050 / 205137-050	37,00 ± 0,40	42,00 ± 0,50
38	105138-050 / 205138-050	38,00 ± 0,50	47,00 ± 0,50
50S	10515S-050 / 20515S-050	47,40 ± 0,50	53,10 ± 0,50
50	105150-050 / 205150-050	50,00 ± 0,50	56,50 ± 0,50